



Metering Module Usage Instructions

Preview

User manuals, setup guides, troubleshooting help, and repair information for Metering Module products. Tip: include the full model number printed on your Metering Module label for the best match. LoRaWAN HAC-MLWA. The Modbus RTU communication module is designed to read data from SHARKY 775 compact ultrasonic energy meters or SCYLAR INT 8 energy calculators manufactured by Diehl Metering, and to share data over the Modbus RTU network using the EIA-485 (formerly RS-485) channel. The module is designed to be. The addition of either symbol to a "Danger" or "Warning" safety label indicates that an electrical hazard exists which will result in personal injury if the instructions are not followed. Obey all safety. If the error LED is lit or flashing in the XCethernet version, a fault has occurred. These instructions are intended for technicians who are. ReliaMod™ main breaker or main fusible switch modules are all UL listed and consist of a single means of disconnect and overcurrent protection. THE SALES CONTRACT CONTAINS ALL OBLIGATIONS OF SIEMENS INDUSTRY, INC. THE WARRANTY CONTAINED IN THE CONTRACT BETWEEN THE PARTIES IS ature to 14°F to 149°F (-10°C to 65°C). Measurement Category III (CAT III), Mains Supply Voltage Fluctuations up to 10%.

These instructions are intended for technicians who are responsible for the installation, connection and servicing of the devices.

To read a digital electric meter, read the series of large numbers near the center of your

METER MODULES: Hang meter modules on the mounting rails, loosen all of the main bus joint bolts, and slide the meter modules

If there are configured meter modules in 3 - Pole selection in the Multi-Pole configuration page and the user changes the Voltage

When installing the Smart Meter in a switch cabinet or similar enclosure, make sure that it is of the appropriate safety class and that

All ReliaMod™ main modules are suitable for service entrance applications and consist of N3R outdoor enclosures and horizontal

Increasing meter functionality, declining costs of meters, and a growing recognition of the value of metered data also contribute to the

Eaton



Metering Module Usage Instructions

The meter stack modules employ a one-piece bushbar construction to each socket, as well as one-piece cross bus to each tenant

delta® Solenoid Metering Pump Control Module delta® Target group for these supplementary instructions: trained and qualified

Dimensions X, Y, Z and V are provided in Tables 1 for main-modules and Table 2 for meter-modules. Once dimension A is

This document provides detailed information and instructions to ensure that people can use the machine safely and efficiently. The

1.2 Product Overview The Eaton Power Xpert® Multi-Point Meter (PXMP Meter) offers a highly modular approach to high density

Establish the required height of the centerline of the bottom meter socket, per the utility company specifications. Determine the

Optional: (4) 1/4-20 Screws and nuts provided with meter stack modules. Tighten nuts securely. Main units with prefix WMC, WMTB

SEM3™ - Embedded Micro Metering Module™ Siemens Embedded Micro Metering Module (SEM3) is a modular metering solution

Web: <https://bssoda.pl>

